

MOLYKOTE®

DUPONT™

Smart Lubrication™ for vehicle electrical systems



Design for increased electrification, connectivity and reliability

Meet your critical lubrication requirements for advanced electrical systems design with MOLYKOTE® brand specialty lubricants from DuPont. With our in-depth expertise, a heritage of innovation, problem-solving collaboration, and reliable global supply and technical support, these high-performance *Smart Lubrication*™ solutions are precisely formulated and application-matched to help you achieve:

- **Energy efficiency** with reduced friction losses and increased wear control
- **Comfort and design** with enhanced smoothness and reduced noise and vibration
- **Safety** with added component reliability, less wear and more corrosion resistance
- **Sustainability** with increased process efficiency and durable component service life

Design for increased electrification, connectivity and reliability with a choice of MOLYKOTE® brand *Smart Lubrication*™ solutions:

- **Greases** with special additives to resist water washout, evaporation or oxidation
- **Silicone compounds** for light-load lubricating and sealing in extreme temperatures
- **Anti-seize pastes** with high levels of lubricating solids for heavy loads and slow speeds
- **Anti-friction coatings** for clean dry-film lubrication to control friction, wear and noise
- **Solids and powders** for plastics lubrication and specialized friction-control additives
- **Oils and dispersions** with performance additives in synthetic or mineral blends

Innovate with smart science

Proven, effective MOLYKOTE® brand *Smart Lubrication*™ solutions can help you meet vehicle electrical systems design goals for connected reliability innovation:

Reduce friction and wear; increase service life

- Alternator and fan clutch bearings
- Actuators and motors
- Engine and emission controls
- Starter motor gears, over-running clutches

Reduce squeaks, rattles, unwanted noise and vibrations

- Electric parking brake
- Switches, audio and media controls
- Window regulators

Improve assembly and disassembly

- Spark plug boots, ignition switches
- Threaded fasteners, clips
- Wiring harness connectors





Smart Lubrication™ selection guide: Electrical systems applications

APPLICATION	DESIGN NEED	POTENTIAL SOLUTION(S)	PRODUCT HIGHLIGHTS
Actuators, motors	Reduced friction, wear and noise	MOLYKOTE® YM-102 Grease	Synthetic PAO grease offers low seepage for lubricating plastic components
		MOLYKOTE® EM-50L Grease	Synthetic grease with good noise-damping properties
Alternator, fan clutch bearings	Provide long-term lubrication with reduced friction, wear and noise	MOLYKOTE® FS-841 Grease	Low-consistency fluorosilicone grease for solvent-resistant, high-speed lubrication
		MOLYKOTE® G-5025 Grease	Silicone grease for extended durability in over-running clutches
Diesel engine glow plug controllers	Improved water and corrosion resistance	MOLYKOTE® 4 Electrical Insulating Compound	Greaselike silicone with good dielectric strength, water repellency, oxidation resistance
Electric parking brake	Long-term lubrication with improved performance	MOLYKOTE® E Paste	Synthetic paste with several types of special solid lubricants
		MOLYKOTE® D-708 Anti-Friction Coating	Heat-cured, PTFE-based AFC with excellent corrosion protection
Electronic transmission actuator	Reduced friction and corrosion potential	MOLYKOTE® BR-2 Plus High Performance Grease	Mineral-oil-based grease with solid lubricants and extreme-pressure additives
Engine throttle, emission controls	Reduce friction and wear	MOLYKOTE® HP-300 Grease	PFPE grease with excellent heat, fuel and oil resistance
Fasteners, clips	Proper torque, assembly ease	MOLYKOTE® D-96 Anti-Friction Coating	Air-drying, water-based coating provides low coefficient of friction with light loads
Spark plug boots, ignition switches	Improved water resistance	MOLYKOTE® G-5008 Dielectric Grease	Silicone grease designed for rubber and ceramic pairings
Starter motor gears, spline shaft, clutch	Reduced friction, wear and noise	MOLYKOTE® G-1021 Grease	Synthetic-oil-based grease for extremely low startup and running frictional resistance
		MOLYKOTE® D-7409 Anti-Friction Coating	Heat-cured dry-film lubricant with excellent adhesion, corrosion protection and low friction, even at high temperatures
		MOLYKOTE® 33L Extreme Low Temperature Grease	Silicone-based grease with excellent low-temperature resistance
		MOLYKOTE® G-5025 Grease	Silicone grease for extended durability in over-running clutches
Switches, audio and media controls	Enhanced smoothness and reduced noise	MOLYKOTE® E Paste	Synthetic-oil-based paste with solid lubricants and excellent materials compatibility
		MOLYKOTE® EM-30L Grease	Synthetic grease with PTFE or other solids for lubricating plastic components
		MOLYKOTE® G-1057 Grease	Low-bleed synthetic grease with excellent plastics compatibility
Window lift regulators	Reduced friction, wear, vibration and noise	MOLYKOTE® EM-60L Grease	Synthetic grease suitable for low-temperature lubrication of plastics
		MOLYKOTE® 33L Extreme Low Temperature Grease	Silicone-based grease with excellent low-temperature resistance
Wiring/harness connections	Protection from moisture and fretting corrosion	MOLYKOTE® L-8030 Grease	Solid lubricants in fluorinated solvent form quick-drying, nontacky lubricating film
		MOLYKOTE® 111 Compound	Greaselike silicone with excellent water resistance over a wide temperature range

NOTE: These are proven, effective MOLYKOTE® brand *Smart Lubrication™* solutions for vehicle electrical systems design. Contact your MOLYKOTE® representative for product options to meet specialized requirements.



Sustainable design solutions

Enhance your design sustainability with MOLYKOTE® brand *Smart Lubrication*™ solutions from DuPont. To meet key electrical systems design needs, these advanced specialty lubrication technologies can be custom-formulated for specified performance characteristics, regulatory standards and process requirements. Raw materials include base oils such as silicone, mineral or polyalphaolefin (PAO); solid lubricants such as molybdenum disulfide (MoS₂) and polytetrafluoroethylene (PTFE); thickeners such as lithium; and various performance additives to inhibit rust, resist wear or withstand extreme pressure.

- MOLYKOTE® brand anti-friction coatings (AFCs) provide clean and dry long-term lubrication for starter motors, threaded fasteners and assembly clips.
- MOLYKOTE® brand specialty greases help reduce friction, wear, noise and corrosion on alternators, connectors, window regulators and adjustable-component actuators.

Smart Lubrication™ solutions for other vehicle systems

In addition to the MOLYKOTE® brand *Smart Lubrication*™ solutions for electrical systems design featured in this selection guide, DuPont also offers proven, effective lubricants for these vehicle systems:

- Chassis and brakes
- Exterior
- Interior
- Powertrain

MOLYKOTE®

Learn more: Contact us

To learn more about MOLYKOTE® brand specialty lubricants and proven, effective *Smart Lubrication*™ solutions to drive connected reliability innovation in vehicle electrical systems design, contact your MOLYKOTE® Technical Representative or visit molykote.com.

DuPont™, the DuPont Oval Logo, and all products, unless otherwise noted, denoted with ™, SM or ® are trademarks, service marks or registered trademarks of affiliates of DuPont de Nemours, Inc. © 2019 DuPont de Nemours, Inc. All rights reserved.

The information set forth herein is furnished free of charge and is based on technical data that DuPont believes to be reliable and falls within the normal range of properties. It is intended for use by persons having technical skill, at their own discretion and risk. This data should not be used to establish specification limits nor used alone as the basis of design. Handling precaution information is given with the understanding that those using it will satisfy themselves that their particular conditions of use present no health or safety hazards. Since conditions of product use and disposal are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information. As with any product, evaluation under end use conditions prior to specification is essential. Nothing herein is to be taken as a license to operate or a recommendation to infringe on patents.

