




Vacuum plugs
Vacuum regulation
Vacuometers
Quick plugs
Other plugs & adapters
Pre-assembled manifolds



VACUUM PLUGS

VACUUM REGULATION

VACUOMETERS











1. QUICK SELF-CUTTING **VACUUM PLUG -1/4» MALE**

Red silicone seal Blue anodized nut The film is not entirely cut so that the seal does not go away

ACPRISE-VIDEAUT01/4M

2. ACPRISE-VIDEAUT050

4. 1/4" MALE **VACUUM REGULATOR**

ACREGUL-MAN-1/4-VACU

5. 1/8" MALE **VACUUM REGULATOR**

ACREGUL-MAN-3/8





7. VACUOMETER

ACVACU63-1/4MCUP

+ Suction cup

8. VACUOMETER 1/2" Male vacuometer Ø 100 mm

ACVACU100-1/2M

9. DIGITAL VACUOMETER ACVACU76ELEC-1/2M

EXAMPLES

QUICK PLUGS



QUICK MALE PLUG 1/4 G | with shut-off valve

ACAUTO-M-1/4M



QUICK FEMALE PLUG 1/4 G | with shut-off valve

ACAUTO-M-1/4F



QUICK MALE PLUG 1/2 G | with shut-off valve

ACAUTO-M-1/2M



ACAUTO-LAITON-M-1/4F



ACAUTO-LAITON-F-1/4F



3/8 F | with shut-off valve





ACAUTO-F-TUB10M



210°C



QUICK MALE PLUG 1/4 G | with shut-off valve





QUICK FEMALE PLUG 1/4 | with shut-off valve Viton seal + PTFE

ACAUTOECO-F-1/4F



240°C



210°C

AUTOCLAVE

STANDARD

OTHER PLUGS & ADAPTERS

	(f)			REF.	8
Y		1/4"F DOUBLE Y PLUG		ACRAC-Y1/4F	
Plugs	100	3/8"F DOUBLE	Y PLUG	ACRAC-Y3/8F	Un
				7,0,1,0	
X	5.10			REF.	
Plugs		1/4"F TRIPLE X PLUG		ACRAC-X1/4F	
	1	3/8"F TRIPLE X PLUG		ACRAC-X3/8F	
T Plugs				REF.	
	1	1/4"F DOUBLE T PLUG		ACRAC-T1/4F	
		3/8"F DOUBLE T PLUG		ACRAC-T3/8F	
				REF.	
Plugs for		1/4"M PLUG		ACMANCHON1/4TUB08	
Tubes	1	1/4"M PLUG		ACMANCHON1/4TUB10	
		3/8"M PLUG		ACMANCHON3/8TUB10	
Adapters				REF.	
		1/2"F - 3/4"M ADAPTER		ACADAPT1/2F3/4M	
	0	1/4"F - 3/8"M ADAPTER 1/4"M - 3/8"M ADAPTER 1/4"F - 3/8"F ADAPTER		ACADAPT1/4F3/8M	
	80			ACADAPT1/4M3/8M	
				ACADAPT1/4F3/8F	
	8	1/4"M - 3/8"F ADAPTER		ACADAPT1/4M3/8F	
				REF.	
Caps		1/4" MALE CAP		ACBOUCH6PC1/4M	
		6 Hexagon socket screw		ASSOCIATION OF 1/4/191	
	7. 0	1/4" MALE CAP		ACBOUCH6P1/4M	
	~			DEE	
Sleeve		1/4" FEMALE S	LEEVE	REF. ACMANCH1/4F	F1/4F
Hose end	3/4" female threaded fitting	3/4" male threaded fitting	3/8" male threaded fitting	20 mm Grooved coupling	10 mm Grooved coupling
coupling	ACRAC-GEKA-	ACRAC-GEKA-	ACRAC-GEKA-	ACRAC-GEKA-	ACRAC-GEKA-
	3/4F Female hose end coupling QAC94	3/4M Female hose end coupling QAC95	3/8M	Grooved hose end coupling for 20 mm ID hose.	Grooved hose end coupling for 10 mm hose.

PRE-ASSEMBLED MANIFOLDS

WITH VALVES ACMANI-4V-1/2 ACMANI-4V-1/4 1/2" 4 inlets 1/4" 4 inlets ACMANI-5V-1/2 ACMANI-5V-1/4 ACMANI-5S-1/4 ROOM TEMPERATURE WITHOUT VALVES ACMANI-4S-1/4 ACMANI-4S-1/4 ACMANI-5S-1/4 Max. T° 180°C

PRESSURE INTENSIFYING SEAL



CO-RD4323-1315

Advantages:

- Intermediate debulking applications and curings
- Oven and Autoclave compatible
- Reusable
- Easy and quick implementation

Intensifying triangular silicone seal for right-angled corner

In order to improve the pressure in small angles, we provide a triangular seal with a high shore hardness, to be placed when vacuuming between the release film and the bleeder / breather.

